



Technical Data Sheet		Product Name TPE compounds
Product Type Polyethylene Compound	Product Grade 10901CLA	

Product Description

10901CLA is a thermoplastic elastomer derived from polyolefin raw materials. This product is specifically designed for continuous compression molding and is formulated for use as a gasket material in metal crown caps for beverage applications.

Typical Application

- Pasteurization process
- Beverage: Carbonate soft drink, Alcohol beverage with less than 20% alcohol content

Product Characteristics

- Excellent process ability and good sealing property
- Non heavy metal

International Compliance

- European Commission Regulation (EU) No.10/2011 **
- US FDA 21 CFR 177.1210 ***
- Notification of the Ministry of Public Health (No.435) B.E. 2565 (2022) (List no.1)

*Overall migration in 3% acetic acid, 10% ethanol, 50% ethanol under OM3

**Specific migration of heavy metal and PAAs under OM3

***120°F and 150°F for 2 hours (Distilled water, 8% alcohol)

Physical Properties

Properties	Test Method	Typical Value	Unit
Specific Gravity	ASTM D 792	0.93	-
Hardness Shore A @15 sec	ASTM D 2240	95	
Tensile Strength	JIS K6723	147	kgf/cm ²
Elongation at Break	JIS K6723	652	%
Melt Flow Rate at 190 °C and 2.16 kg	ASTM D 1238	6.3	g/10 min

Note: • The given values are typical value measured on the product. Values herein are not to be constructed as a product specification.



Technical Data Sheet		Product Name TPE compounds
Product Type Polyethylene Compound	Product Grade 10901CLA	

Processing Guidelines

The actual processing condition depends on each extruder machine type, screw type and also output needed etc. Generally, temperature at extruder should be around 150-180°C as sequence from feed throat to die head. The exceed temperature than 190°C might affect to appearance, color and typical property.

Product Technical Assistance

For technical assistance or further information on this product or any other SCG Chemicals' products, contact your SCG Chemicals technical services at the address as specified below.

Product Available Form

- Pellet

Product Packaging

- 20 kg loose bag
- 900 kg Octabin box

Storage

- Store in original container in tidy according to the manual of Handling and Storage from Thai Polyethylene Co., Ltd.
- Product(s) should be stored in dry and dust free location at temperature below 50 °C and protected from direct sunlight and/or heat, well-ventilated area, away from incompatible materials and food and drink, as this may lead to quality deterioration, which results in odour generation and colour changes and can have negative effects on the physical properties of this product.
- Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.
- The storage area should be stable and not be slopped.

Safety

- The product is not classified as a hazardous material.
- Please see our Material Safety Data Sheet for details on various aspects of safety, recovery, and disposal of the products;
for more information, contact your SCG Chemicals technical services.



Technical Data Sheet	Product Name TPE compounds
Product Type Polyethylene Compound	Product Grade 10901CLA

Recycling

- The product is suitable for recycling using modern methods of shredding and cleaning. In-house production waste should be kept clean to facilitate direct recycling.
- Please see our Material Safety Datasheet for details on various aspects of safety, recovery and disposal of the products;
for more information, contact your SCG Chemicals technical services.

Related Documents

- The latest version of this document will be available at our website, www.scgchemicals.com, or can be obtained from the SCG Chemicals technical services.
- The following related documents are available on request, and represent various aspects on the usability, safety, recovery and disposal of the product.
 - Safety Data Sheet
 - Declaration of Compliance

Disclaimer

- The Applications specified herein is for reference only.
- It is customer's responsibilities to inspect and test the product for suitability of the customer's own use and purpose. The customer is responsible for appropriate, safe, legal use, processing and handling of the product.
- To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication. We however do not assume any liability whatsoever for the accuracy and completeness of the information contained herein.
- We make no warranties which extend beyond the description herein. Nothing herein shall constitute any implied warranty of merchantability or fitness for a particular purpose.
- No liability can be accepted in respect of the use of the product in conjunction with other materials. The information contained herein relates exclusively to the product when it is not used in conjunction with any third party's materials.